



# RIGGA Pulley Hoist Utility System 15m

**P&P RIGGA Pulley Hoist 90407MK2** Utility System - For work positioning / rescue Raising and lowering vertically. The system may be controlled by the user or by a second person on behalf of the user. When the user is lowered, the one way pulleys lock adding friction, which then requires only a small effort to hold the load. When the user is raised, the pulley wheels turn, minimising friction. The system gives a 4:1 advantage. Safe Working Load - 250kg

- **Pulley:**

One Way Pulleys  
Length - 170mm  
Width - 84mm  
Thickness - 60mm  
Weight - 700g  
Minimum Breaking Load - 45kN  
Finish - Anodised  
BS EN 12278

**Rope:**

Diameter - 11mm  
Weight - 75g/m  
Static Breaking Strength - 34kN  
100% Polyamide  
BS EN 1891

**Ascender:**

Length - 217mm  
Width - 87mm  
Thickness - 30mm  
Weight - 350g  
Aluminium Alloy  
Stainless Steel Cam  
BS EN 567

**Karabiners**

Captive Eye Kwiklock  
Offset 'D' Kwiklock  
Oval Link Screw Gate x 2



- **Rigga Pulley Hoist** comes complete with Anchor Strop and Kit Bag – total kit weight 7.7kg