



Designers, Manufacturers & Suppliers of Quality Height Safety &
Rescue Equipment, Training & Consultancy

P&P TOOL RETENTION SYSTEM INSTRUCTIONS FOR USE

The 'Unique' Tool Retention System (TRS) will, if used correctly, save you both time and money.

Please follow these simple User Instructions.

- Identify where the TRS is best attached to your Belt or Full Body Harness.
- If you want to attach to a Waist Belt, simply feed the webbing through the slot on the back (max 50mm).
- If you want to attach anywhere on your Full Body Harness, simply undo the screw on the slot at the back, open and fit to the webbing. The screw must now be screwed back in, ensuring it has not been cross-threaded and it as tight as possible.
- Attach the hook to your work appliance, ensuring the hook latch is fully closed.
- Do not attach a work appliance heavier than 1.5kg.
- Always remember to check your TRS before each use. Ensure the cord retracts freely (without a work appliance attached)
- Check the attachment hook is free from cracks and the latch works correctly. Check the cord for signs of fraying. Do not use if damaged.

P&P Safety Limited
131 New John Street, Aston, Birmingham B6 4LD England
Tel: +44 (0) 121 359 4561 (Sales)
Fax: +44 (0) 121 359 4136
website: www.ppsafety.co.uk email: sales@ppsafety.co.uk

Registered in England No. 01493537